




STEPS FOR CONNETING EDGINGS TOGETHER




4A. CUT APPROXIMATELY 5 INCHES OFF THE ROUND TUBE FROM ONE OF THE EDGING.



4B. USE A CONNECTOR TUBING TO ALIGN BOTH ENDS OF EDGING.



4C. CONNECT THE TWO EDGING TOGETHER



4D. FOLLOW STEP "3" TO SECURE THE EDGING

1. DIG A 4-5 INCH DEEP TRENCH ALONG EDGE OF LAWN.
2. PLACE EDGE EX EDGING INTO TRENCH. THE BOTTOM "V" LIP OF THE EDGING SHOULD BE FACING GROUND COVER OR PLANTING AREA.
3. POUND STAKE, PIERCING INTO EDGING AT A 45 DEGREE ANGLE. INSTALL STAKE EVERY 5' (CLOSER AT CURVES).
4. FOLLOW STEPS 4A - 4D TO CONNECT EDGING.
5. FILL BACK TRENCH AND TAMP DOWN.

INCLUDED ACCESSORIES FOR EACH EDGE EX 20' BLACK TUBE EDGING

DESCRIPTION AND QUANTITY	ACTUAL DIMENSION D x H x L	PRODUCT NUMBER
GALVANIZED METAL STAKE / 4	.62in X 1.8n X 9in 1.6cm X 4.6cm X 22.9cm	100059577
CONNECTOR TUBING / 1	.84in Dia. X 6in 2.13cm Dia. X 15.2 cm	

PRODUCT NUMBER	NOMINAL DESCRIPTION	COLOR	ACTUAL DIMENSION D x H x L	RECOMMENDED ACCESSORIES
100060052	20'	BLACK	1.12in X 5.2in X 20ft 2.84cm X 13.2cm x 6.09m	ALL LISTED ON NEXT CHART

EDGE EX BLACK TUBE EDGING DETAIL-415

MADE IN USA by EPIC PLASTICS
104 E. TURNER RD, LODI CA 95240
www.epicplastics.com

EDGE EX EDGING IS INTENDED FOR NON-STRUCTURAL USE ONLY