



BENDA BOARD® FLEX | TEAK/.76 CM

BENDA BOARD® FLEX

Benda Board® FLEX is a creative landscape solution that is *EASY TO INSTALL*, durable and flexible — Perfect for Mow Strips, Tree Rings, Concrete Form Boards, Rock Garden Definition or a Pathway Border.



BLACK

TEAK

PRODUCT #	PRODUCT	AVAILABLE SIZES (Metric / Actual / Nominal Size)	MIN. ORDER
100081345	Benda Board® FLEX Black	.30 in x 3.3 in x 16 ft (.76 cm x 8.38 cm x 4.88 m)	96 packs/pallet
100081344	Benda Board® FLEX Teak	.30 in x 3.3 in x 16 ft (.76 cm x 8.38 cm x 4.88 m)	96 packs/pallet

*4 Stakes Included

INSTALLATION INSTRUCTIONS

BENDA BOARD® FLEX

BENDA BOARD® FLEX IS INTENDED FOR NON-STRUCTURAL USE ONLY

BEFORE YOU BEGIN

Unroll the coiled edging onto an even surface, preferably in the sun. Add a weight to each end of the board. When the board stays flat without help of weights, you are ready to proceed.



DESIGN LAYOUT

Create the desired design for your installation location using a garden hose or rope.



EXCAVATION

Dig a trench in the shape of your design, approximately 3 inches deep.



Drive the stakes into the trench every 4-5 feet.




INSTALLATION

Securely press the Benda Board® Flex into the initial stake clip, and repeat this action at each subsequent stake along the way.

If needed, use coarse woodworking tools to cut excess board.

For final height adjustment, use rubber mallet to tap board at stakes.



BACKFILL

Backfill the space on both sides of the board, concealing the stakes, and compact the soil or rock to ensure stability.